

 深圳市汇科源电子科技有限公司 Shenzhenshi Huikeyuan Electronic Tech.co., LTD		REVISION (版本)	A0
		DATE (日期)	2026.08.28
PART NUMBER (产品编号)	HKY-8USB-C-PD65W	CUSTOMER NAME AND MODEL (客户名称和型号)	

SPECIFICATION FOR APPROVAL

产 品 承 认 书

CUSTOMER / 客 户: _____

CUSTOMER MODEL NO. / 客户型号: _____

SAMPLE NO. / 样品单号: _____

SERIES PRODUCTS / 产品系列: _____

PRODUCT NAME / 产品名称: HKY-8USB-C

OUR MODEL NO. / 机种型号: HKY-8USB-C-PD65W

Color / 颜色: Black/黑色 DATE / 日期: 2026.08.28

CUSTOMER APPROVED SIGNATURE 客户确认		

Designed by 制 作	Checked by 审 核	Approved by 批 准
张 繁	汪 海 波	

Please to sign back after you confirm!

承认书确认后请回签一份!

 深圳市汇科源电子科技有限公司 Shenzhenshi Huikeyuan Electronic Tech.co., LTD		REVISION (版本)	A0
		DATE (日期)	2026.08.28
PART NUMBER (产品编号)	HKY-8USB-C-PD65W	CUSTOMER NAME AND MODEL (客户名称和型号)	

Rev. List/版本目录			
Rev. /版本	Date/日期	Description/描述	Design/制订
A0	2026.08.28	New Rev. /新版本	

Content/目录

1.	Scope (适用范围)	4
2.	Type-C Support and USB-PD Support (Type-C 支持和 USB-PD 支持)	4
3.	Quote Criterion (引用标准)	4
3.	Input Characteristics (输入特性)	4
3.1.	Rated Input Voltage (额定输入电压)	4
3.2.	Rated Input Current (输入电流)	4
4.	Output Characteristics (输出特性)	4
4.1.	Rated Output Voltage (输出额定电压电流)	4-5
4.2.	Rated Power (额定功率)	5
4.3.	Output Ripple and Noise (输出纹波、噪音)	5
4.4.	Protection (保护)	5
4.4.1.	Over Current Protection (过流保护)	5
4.4.2.	Short Circuit Protection (短路保护)	5
4.4.3.	Thermal protection (过温保护)	6
4.5.	Temperature Rise (温升)	6
5.	Environmental Requirement (环境要求)	6
5.1.	Operating Temperature (工作温度)	6
5.2.	Storage Temperature (储藏温度 8H)	6
5.3.	Operating Humidity (工作湿度)	6
5.4.	Storage Humidity (储藏湿度)	6
6.	Mechanical Requirement (机械要求)	6
6.1.	Drop Test (跌落试验)	6-7
6.2.	Salty Fog Test for Metal Part (五金件盐雾实验)	7
6.3.	Plug and pull experiment (插拔实验)	7
7.	Mechanical Characteristics (机械性能)	7
7.1.	Appearance (外观)	7
7.2.	Case/Resin Materials (外壳材质)	7
8.	Environmental Performances(环境性能)	8

 深圳市汇科源电子科技有限公司 Shenzhenshi Huikeyuan Electronic Tech.co., LTD		REVISION (版本)	A0
		DATE (日期)	2026.08.28
PART NUMBER (产品编号)	HKY-8USB-C-PD65W	CUSTOMER NAME AND MODEL (客户名称和型号)	

8.1. Operating at the Lower temperature (低温工作实验)	8
8.2. Operating at the High Temperature (高温工作实验)	8
8.3. Storage at the Lower Temperature(低温放置)	8
8.4. Storage at the Higher Temperature (高温放置)	8
8.5. Storage at High Temperature and High Humidity with the Adaptor Turned on(高温高湿度放置)	8
8.6. Storage at low Temperature and Low Humidity with the Adaptor Turned on(低温低湿度放置)	8
9. Photograph of the Product (产品外观图)	9
10. Precautions (注意事项)	9
10.1. Power input polarity(电源输入电源极性)	9
10.2. Input AC-DC power supply requirements (输入 AC-DC 电源要求)	9
10.3. LED indicator function(LED 指示功能)	9

 深圳市汇科源电子科技有限公司 Shenzhenshi Huikeyuan Electronic Tech.co., LTD		REVISION (版本)	A0
		DATE (日期)	2026.08.28
PART NUMBER (产品编号)	HKY-8USB-C-PD65W	CUSTOMER NAME AND MODEL (客户名称和型号)	

1. Scope (适用范围)

The specification shall be applied to the field of IT and AV equipment
 本规范应适用于 IT 和 AV 设备领域。

2. Type-C Support and USB-PD Support (Type-C 支持和 USB-PD 支持)

USB-C 3.0A, PD2.0 65W

PD3.0 PPS 5.00-11.0V 55W

APPLE2.4A BC1.2DCP

QC3.0 5V 9V 12V QC4+

SAMSUNG-AFC 5V 9V 12V 25W

HUAWEI-FCP 5V 9V 12V 24W

SCP 3.3-10.V 5.0A 023W

3. Quote Criterion (引用标准)

2.1 EMI STANDARD (EMI 标准)

EN55032:2015+A11:2020+A1:2020

EN55035:2017+A11:2020

EN IEC 61000-3-2:2019+A1:2021+A2:2024

EN61000-3-3:2013+A1:2019+A2:2021

3 Input Characteristics (输入特性)

3.1 Rated Input Voltage (额定输入电压)

It is normal for 21Vdc to 24Vdc input DC voltage.
 (额定输入直流 21V~24VDC)

3.2 Rated Input Current (额定输入电流)

It is normal for 28.0A Max input Current
 (额定输入电流 28.0A 最大)

4 Output Characteristics (输出特性)

4.1 Rated Output Voltage Current (输出额定电压电流)

 深圳市汇科源电子科技有限公司 Shenzhenshi Huikeyuan Electronic Tech.co., LTD			REVISION (版本)	A0
			DATE (日期)	2026.08.28
PART NUMBER (产品编号)	HKY-8USB-C-PD65W	CUSTOMER NAME AND MODEL (客户名称和型号)		

Model 型号	4.1 Output Voltage 输出电压	4.1 Min Load 最小负载	4.1 Output Current 输出电流	4.1 Load Regulation 负载调整	4.1 Line Regulation 线性调整	4.1 Output Voltage Range 输出电压范围	4.2 Rated Power 额定功率	4.3 Ripple/Noise (p-p) 纹波噪声	4.4.1 Over Current Protection 过流保护
HKY-8USB-C-PD65W (C1 to C8)	5V	0A	3A	±5%	±1%	4.75V-5.40V	15W	150mV Max	4.3A Max
	9V	0A	3A	±5%	±1%	8.55V-9.45V	27W	150mV Max	4.3A Max
	12V	0A	3A	±5%	±1%	11.4V-12.6V	36W	150mV Max	4.3A Max
	15V	0A	3A	±5%	±1%	14.25V-15.75V	45W	150mV Max	4.3A Max
	20V	0A	3.25A	±5%	±1%	19.0V-21.0V	65W	150mV Max	4.6A Max

4.2 Rated Power (额定功率)

This adapter is capable to support Rated MaxPower continuously at all specified conditions. Note: the test shall be made under the following conditions, unless otherwise specified: Ambient Temperature 25°C, Relative Humidity 35~85%RH Air Pressure 86~106kPa

(不同状态下输出额定最大功率，在无特别指定条件下,测试温度为 25°C、湿度为 35~85%RH、气压为 86~106kPa)

4.3 Output Ripple and Noise (输出纹波、噪音)

DC Input 21V. 24V Output ripple voltage is less Measured methods:Performed by 20MHz bandwidth in oscilloscope. Applied 0.1uF ceramic capacitor and 10uF electrolytic capacitor across output connector terminals Measured at the end of DC cable.

(DC 输入 21V 24V 输出端并 0.1uF 与 10uF 电容，限制示波器带宽 20MHz 时)

4.4 Protection (保护)

4.4.1 Over Current Protection (过流保护)

Output overcurrent protection current is limited and less than the maximum value
输出过流保护电流被限制且小于最大值

4.4.2 Short Circuit Protection (短路保护)

The adapter is protected that a short happened between the ouput terminals and shall not result in a fire hazard ,any damage to this adapter and will be normal operation automatically while the short is trmoved.
当输出短路时,产品输入功率降低且不会损伤,当短路情况解除后,产品将会自动恢复正常

 深圳市汇科源电子科技有限公司 Shenzhenshi Huikeyuan Electronic Tech.co., LTD		REVISION (版本)	A0
		DATE (日期)	2026.08.28
PART NUMBER (产品编号)	HKY-8USB-C-PD65W	CUSTOMER NAME AND MODEL (客户名称和型号)	

4.4.3 Thermal protection (过温保护)

Output over load,the main components of temperature more than 125°C protection (shell temperature was 77°C) xirxuit protection,the main components of the temperature dropped to 50°C below normal output

输出过载时,主要元件温度超过 125°C保护(外壳温度≥77°C)电路保护,主要元件温度降到 50°C以下恢复正常输出

4.5 Temperature Rise (温升)

The input voltage of 21-24 Vdc is applied at 25°C, and the shell temperature is less than 77°C at the maximum output load.

(在常温 25°C下输入端施加 21-24Vdc 电压, 输出最大负荷状态下, 机壳温度小于 77°C。)

5 Environmental Requirement (环境要求)

5.1 Operating Temperature (工作温度)

-10°C TO 40°C Full load, Normal operation.满载,正常工作.

5.2 Storage Temperature (储藏温度 8H)

-25°C TO +70°C With package/带外壳

5.3 Operating Humidity (工作湿度)

5%(0°C)~90%(40°C),RH,72Hrs,Full load, Normal operating.

5%(0°C)~90%(40°C), 湿度, 72 小时,满载,正常工作

5.4 Storage Humidity (储藏湿度)

5% ~ 95% RH. Non-condensing

6 Mechanical Requirement (机械要求)

6.1 Drop Test (跌落试验)

from 100cm height to the most likely to cause adverse results to the horizontal position of the surface drop test bed three times, the adapter in addition to surface scratches, it should be no dysfunction can cause the adapter and other potentially the harm. (Horizontal surface of the test rig shall be composed of at least 13mm thick hardwood

 深圳市汇科源电子科技有限公司 Shenzhenshi Huikeyuan Electronic Tech.co., LTD		REVISION (版本)	A0
		DATE (日期)	2026.08.28
PART NUMBER (产品编号)	HKY-8USB-C-PD65W	CUSTOMER NAME AND MODEL (客户名称和型号)	

installed in two layers of plywood, each layer of plywood thickness 19-20mm, and then placed on a cement base or equivalent on the ground inelastic)

(从 100cm 高处、以可能对其造成最不利结果的位置跌落至水平表面试验台 3 次, 适配器除表面有擦伤外, 应该没有任何功能障碍和其他方面能导致适配器产生潜在的危害。(水平表面试验台应是由至少 13mm 厚的硬木安装在两层胶合板上组成, 每一层胶合板的厚度为 19-20mm, 然后放在一水泥基座上或等效的无弹性的地面上)

6.2 Salty Fog Test for Metal Part (五金件盐雾实验)

Experiment condition, Salty water thickness: 5%, Equipment Temperature: 35 ~ 40°C, put the adapter(unpacking) in the test equipment for 24h, after 24h recovery at 25°C checking the appearance, the metal parts have no erode and rust.

(盐雾试验要求: 调制 (工业盐) 盐水的浓度为 5%, 设备温度设置为 35~40°C, 适配器不包装, 放入盐雾试验设备中持续喷雾 24 小时, 试验结束后取出, 在常温下搁置 24 小时, 再检查适配器外观; 要求外露金属及电镀件不生锈。)

6.3 Plug and pull experiment (插拔实验)

Plug and xommector after normal plug 10 times, plug each insert strength is not more than 30N, pull out in 10N to 50N after between continuous pull plug 3000 times Appearance is allowed to have mild damage, but conducting performance is good

(插头与连接器经正常插拔 10 次, 插头每次插入力度不大于 30N, 拔出在 10N-50N 之间后持续插拔 3000 次. 外观允许有轻度损伤, 但对通性能良好)

7 Mechanical Characteristics (机械性能)

7.1 Appearance (外观)

Visual inspection the case have no visual abnormality, no obvious nick, burr and other mechanical damage, outer metal have no rust. Use limit sample to check for any failures.

(目视检查, 无外观异常, 表面无明显划痕、毛刺及其它机械损伤, 外露金属部分无锈, 其他限度根据样品确认。)

7.2 Case/Resin Materials (外壳材质)

(1) Upper shell Flame resistance applies to UL94-V1
(上壳耐燃性遵循 UL94-V1)

(2) Bottom shell: Aluminum spray coating treatment
(底壳: 铝材喷涂处理)

 深圳市汇科源电子科技有限公司 Shenzhenshi Huikeyuan Electronic Tech.co., LTD		REVISION (版本)	A0
		DATE (日期)	2026.08.28
PART NUMBER (产品编号)	HKY-8USB-C-PD65W	CUSTOMER NAME AND MODEL (客户名称和型号)	

8 Environmental Performances(环境性能)

8.1 Operating at the Lower temperature (低温工作实验)

At $-10\pm 2^{\circ}\text{C}$, with the rated voltage 21-24Vdc charged to the primary and unloaded and full load on the secondary, no abnormality in electric and mechanical characteristic, after 2 hours recovery at the room temperature.

(环境温度 $-10\pm 2^{\circ}\text{C}$, 在输入端施加额定电压 21-24Vdc 输出端无负荷与满载状态下, 试验 2 小时, 无特性异常)

8.2 Operating at the High Temperature (高温工作实验)

At $40\pm 2^{\circ}\text{C}$, with the rated voltage 21-24Vdc charged to the primary and unloaded and full load on the secondary. No abnormality in electric and mechanical characteristic after 2 hours recovery at the room temperature.

(环境温度 $40\pm 2^{\circ}\text{C}$, 在输入端施加额定电压 21-24Vdc 输出端无负荷与满载状态下, 试验 2 小时, 无特性异常)

8.3 Storage at the Lower Temperature(低温放置)

At $-25\pm 2^{\circ}\text{C}$, test of non-operated, No abnormality in electric and mechanical characteristic after 2hours recovery at the room temperature.

(在 $-25\pm 2^{\circ}\text{C}$ 非工作状态下进行试验, 试验后常温放置 2 小时后测试无异常)

8.4 Storage at the Higher Temperature (高温放置)

At $70\pm 2^{\circ}\text{C}$, test of non-operated, No abnormality in electric and mechanical characteristic after 2hours recovery at the room temperature.

(在 $70\pm 2^{\circ}\text{C}$ 非工作状态下进行试验, 试验后常温放置 2 小时后测试无异常)

8.5 Storage at High Temperature and High Humidity with the Adaptor Turnedon(高温高湿度放置)

At $40\pm 2^{\circ}\text{C}$, 90~95%RH, test of operating 48hours, no abnormality in electric and mechanical characteristic, after 4hours recovery at the room temperature.

(在 $40^{\circ}\text{C}\pm 2^{\circ}\text{C}$, 90~95%RH, 非工作状态试验持续 48H, 试验后常温放置 4 小时测试特性无异常)

8.6 Storage at low Temperature and Low Humidity with the Adaptor Turnedon(低温低湿度放置)

At $-10^{\circ}\text{C}\pm 2^{\circ}\text{C}$, 10%~40%RH, test of operating 48hours, no abnormality in electric and mechanical characteristic, after 4hours recovery at the room temperature.


(在 $-10^{\circ}\text{C}\pm 2^{\circ}\text{C}$, 10%~40%RH, 非工作状态试验持续 48H, 试验后常温放置 4 小时测试特性无异常)

 深圳市汇科源电子科技有限公司 Shenzhen Huikeyuan Electronic Tech.co., LTD		REVISION (版本)	A0
		DATE (日期)	2026.08.28
PART NUMBER (产品编号)	HKY-8USB-C-PD65W	CUSTOMER NAME AND MODEL (客户名称和型号)	

9 Photograph of the Product (产品外观图)

11.1 Enclosure/外壳:

The power supply size: L201.0x W64.7x H31.6mm; 外壳尺寸: 长 201.0x 宽 64.7x 高 31.6mm;



10. Precautions (注意事项)

10.1. Power input polarity: Square for positive, round for negative

电源输入电源极性: 方正圆负

10.2 Input AC-DC power supply requirements: Output voltage 21-24VDC, Output current: 28A minimum

输入 AC-DC 电源要求: 输出电压 21-24VDC, 输出电流: 28A 最小

10.3 LED indicator function

LED 指示功能

A. When the power supply is matched with the device host and protocol, the LED lights up green.

当电源与设备主机与协方议匹配时, LED 亮绿色。

B. When the power supply does not match the device host and protocol, the LED does not light up.

当电源与设备主机与协方议不匹配时, LED 不亮。